

Model 200/225 Mounted Sentry with Outlet Plenum

MADE IN
THE USA



SINCE 1983

Model # SS-200/225-MSP

The **Model 200/225 Mounted Sentry with Outlet Plenum** most commonly exhausts filtered air to a remote location or to create positive pressure environment. The 4" diameter exhaust collar allows air to be exhausted outside or into your central exhaust system or ducting. This unique system when combined with **HEPA filtration** can also be utilized to create positive pressure providing clean air to enclosures or compact clean rooms. This unit has the option of remaining ductless to recirculate filtered air back into the immediate area.

Typical applications for this unit include: *laser marking, printing fumes, soldering fumes, fume/vapor source capture, positive pressure clean room, chemical fume exhaust, enclosed machinery mounting, and many other applications that produce particulate, smoke, dust, and fumes.*

High-quality filter media for this unit is customized depending on the application being performed, but typically includes **HEPA filters** (up to 99.97% efficiency on particles 0.3 microns and larger), **ASHRAE filters** (up to 95% efficiency on particles 0.5 microns and larger), **Activated Carbon**, and **specialty-blended filtration media** [i.e. acid gas, mercury, aldehyde, and ammonia].

The **Mounted Sentry with Outlet Plenum** is available in larger models [SS-300-MSP & SS-400-MSP] and without the outlet plenum [SS-200/225-MS].

Product Features

- **Includes:** mounting brackets
- **Optional:** variable speed controller and hour counter
- Quiet, reliable, low maintenance operation
- Sturdy construction
- Low power consumption
- Simple, quick "no tool" filter change
- Long filter life



Model 200/225 Mounted Sentry with Outlet Plenum



Mounted Sentry with Plenum can be used to exhaust out harmful fumes and particulate.



21221 FM 529 Rd, Cypress, TX 77433
1.800.799.4609 • sales@sentryair.com

www.sentryair.com

Fume & Particulate Removal

Product Specifications



Dimensions are approximate.



21221 FM 529 Rd
Cypress, TX 77433
1.800.799.4609
sales@sentryair.com

www.sentryair.com

Base Unit Dimensions	Length: 10.5" (includes control box) Width: 10" (includes mounting brackets) Height: 22" (includes plenums)
Exhaust Config.	4" diameter
Cabinet Material	16 ga. carbon steel
Weight	Approx. 20 lbs
Air Volume (approximately)	95% ASHRAE: 200: up to 100 CFM 225: up to 130 CFM Pre-Filter + HEPA: 200: up to 80 CFM 225: up to 91 CFM
Electrical	200: 115/1/60, 0.3 amps 220/1/50, 0.2 amps 225: 115/1/60, 0.46 amps 8' grounded power cord with NEMA 5-15P plug
Sound Level (High at 3' from inlet)	200: Approx. 56 dba 225: Approx. 64 dba
Main Filter Options	<i>Depending on the Application:</i> 200 - Chemical: Activated Carbon Specialty-Blended Filter Media [i.e. acid gas, mercury, aldehyde, and ammonia] 225 - Particulate: HEPA [up to 99.97% efficiency on particles 0.3 microns and larger] ASHRAE [up to 95% efficiency on particles 0.5 microns and larger] ULPA [up to 99.9995% efficiency on particles 0.12 microns and larger]
Patent #	5,843,197