12" Mini Ductless Fume Hood

Model # SS-212-DCH

The **12" Wide Mini Ductless Fume Hood** helps protect the operator and environment from hazardous fumes or particulate generated from applications performed within the hood. The compact design makes it an ideal fume extraction solution for containing beakers and test tubes in chemical and/or biological labs or even for small-scale pharmaceutical compounding applications. This lightweight hood provides optimal fume control for field-testing applications because of its ability to be easily transported and its reliable operation. Also as an option, this system can include a removable spill tray for chemical spills.

The **12" Mini Ductless Fume Hood's** powerful fan directs fumes into the filter chamber containing high quality filter media selected depending on the application. Filter media choices include **HEPA** [up to 99.97% efficiency on particles 0.3 microns and larger], **ASHRAE** [up to 95% efficiency on particles 0.5 microns and larger, **Activated Carbon**, and **specialty-blended filtration** [i.e. acid gas, mercury, aldehyde, and ammonia].

Typical uses for the **12" Mini Ductless Fume Hood** include chemical fumes, compounding, soldering, and a variety of applications requiring fume and dust removal. The **Mini Ductless Fume Hood** can provide an effective and economical solution for many commercial, medical, laboratory and industrial applications that require a small containment area.

Our line of ductless fume hoods is not intended for sterile compounding applications.





12" Mini Ductless Fume Hood



12" DCH provides a small workspace for many different applications.

Product Features

- Includes: clear anti-static vinyl curtains
- Optional: variable speed controller (115V only), hour counter, velometer, spill tray, and clean & polish kit
- **Standard Sizes:** 12", 18", 24", 30", 40", 50", 60", and 70" (custom sizes available)
- · Quiet operation
- · Long filter life
- · Simple, quick "no tool" filter change
- Portable and lightweight
- Reliable, low maintenance operation



Product Specifications





Shown with outer dimensions. Dimensions are approximate.



21221 FM 529 Rd Cypress, TX 77433 1.800.799.4609 sales@sentryair.com

www.sentryair.com

Hood Dimensions (D x W x H)	Outer: 10.4" x 13" x 10.6" Interior: 9.6" x 11.6" x 10.2"
Hood Material	Acrylic
Blower Dimensions	10.5"L x 8" W x 8.5" H
Blower Material	16 Ga. carbon steel with polyester epoxy coating on all surfaces
Weight (approximately)	15 lbs
Air Volume (approximately)	80 CFM (varies with filter media)
Inlet Velocities on High (approximately)	Carbon Pre-filter + HEPA Filter - 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter - 60 FPM
Electrical	115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug
Sound Level	55 dba
Maximum Temperature	Operating temperature not to exceed 170° F
Main Filter Options	HEPA (up to 99.97% efficient on particles down to 0.3 microns) ASHRAE (up to 95% efficient on particles down to 0.5 microns) Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)
Warranty	Limited two-year warranty from date of shipment on defects due to materials or workmanship.
Patent #	5,843,197