

70" Ductless Fume Hood - Dual

Model # SS-370-DCH-D



The **70" Wide Dual Ductless Fume Hood** combines powerful air flow of two air cleaners with a sturdy and compact enclosure for optimal respiratory and environmental protection. This fume hood helps protect the operator and environment from hazardous fumes or particulate generated from applications performed within the hood.

The **70" Dual Ductless Fume Hood's** powerful fan directs fumes into the filter chamber containing high quality filter media selected depending on the application. Filter media choices include **HEPA** [up to 99.97% efficiency on particles 0.3 microns and larger], **ASHRAE** [up to 95% efficiency on particles 0.5 microns and larger], **Activated Carbon**, and **specialty-blended filtration** [*i.e. acid gas, mercury, aldehyde, and ammonia*].

Typical uses for the **70" Dual Ductless Fume Hood** include *chemical fumes, pharmaceutical compounding, soldering applications, dust removal, biological applications, and a variety of applications requiring fume and dust removal.* The **70" Dual Ductless Fume Hood** can provide an effective and economical solution for many commercial, medical, laboratory, and industrial applications. For additional visibility, a transparent version is available at extra cost.

Our line of ductless fume hoods is not intended for sterile compounding applications.



70" Ductless Fume Hood - Dual Blowers



70" DCH-D is fitted with dual blowers for increased airflow.

Product Features

- **Includes:** variable speed controller (115V only), clear anti-static vinyl curtains, velometer, and LED light
- **Optional:** Magnehelic Gauge and hour counter
- **Standard Sizes:** 12", 18", 24", 30", 40", 50", 60", and 70" (*custom sizes available*)
- Quiet operation
- Long filter life
- Simple, quick "no tool" filter change
- Portable and lightweight
- Reliable, low maintenance operation



21221 FM 529 Rd, Cypress, TX 77433
1.800.799.4609 • sales@sentryair.com

www.sentryair.com

Fume & Particulate Removal

Product Specifications



Shown with outer dimensions.
Dimensions are approximate.



21221 FM 529 Rd
Cypress, TX 77433
1.800.799.4609
sales@sentryair.com

www.sentryair.com

Hood Dimensions (D x W x H)	Outer: 24" x 72" x 25" Interior: 23.5" x 70" x 24" Access Area: 8" x 70"
Hood Material	Sides: 0.25" white acrylic Base: 0.5" white high density polyethylene Top: 0.5" clear polycarbonate Front Window: 0.25" clear polycarbonate
Blower Dimensions	15.5" L x 13" W x 14.5" H
Blower Material	16 Ga. carbon steel with polyester epoxy coating on all surfaces
Weight	205 lbs
Air Volume (approximately)	350 CFM per blow (varies with filter media)
Inlet Velocities on High (approximately)	Carbon Pre-filter + HEPA Filter – 100 FPM high, 25 FPM low Carbon Pre-filter + Heavy Duty Carbon Filter – 70 FPM high, 20 FPM low
Electrical	115/1/60, 2 amps 220/1/50, 0.75 amps 8' grounded power cord with NEMA 5-15P plug
Sound Level	61 to 66 dba (low to high)
Maximum Temperature	Operating temperature not to exceed 170° F
Main Filter Options	HEPA (up to 99.97% efficient on particles down to 0.3 microns) ASHRAE (up to 95% efficient on particles down to 0.5 microns) Activated Carbon Specialty-Blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)
Warranty	Limited two-year warranty from date of shipment on defects due to materials or workmanship.
Patent #	5,843,197