

## Model 550/500 Industrial Fume Extractor - MP1 Series

# Model # SS-550/500-PYT-MP1

## Product Specifications

### BASE UNIT DIMENSIONS

30" Length  
30" Width  
42.5" Height

### ARM DIMENSIONS

12' L x 6" Dia. Fire-Retardant Python Flex Hose  
w/Magnetic Hood

### CABINET MATERIAL

16 ga. Carbon Steel

### WEIGHT

Approximately 190 lbs. *without* Filters.  
Approximately 282 lbs. *with* Filters Installed.

### AIR VOLUME

Variable Speed Control Standard on 115V  
On/Off Toggle Switch Standard on 220V  
550 - Up to 480 CFM High w/ Micro-Pleat Series 1 Particulate Filters  
500 - Up to 375 CFM High w/ Micro-Pleat Series 1 Particulate Filters

### ELECTRICAL

115/1/60, (550) Approx. 10.7 Amps, (500) Approx. 2.5 Amps  
220/1/50, (550) Approx. 5 Amps, (500) Approx. 1.5 Amps  
8' grounded power cord with NEMA 5-15P Plug

### SOUND LEVEL

550 - Approximately 72 dba (High) at 3'  
500 - Approximately 65 dba (High) at 3'

### FILTRATION

(4) MERV 16 Micro-Pleat Series 1 Particulate Filters

### WARRANTY

Limited two-year warranty from date of shipment  
on defects due to materials or workmanship.  
U.S. PATENT #61563228 Pending



## Product Features

- Variable Speed Controller Included (115V only)
- Reliable, Low Maintenance Operation
- No Exterior Ducting Required
- Magnehelic Gage Included
- Heavy-Duty Casters & Portability Handles
- Long Filter Life
- Cleanable Filters
- 360° Rotating Source-Capture Arm
- Simple "No Tool" Filter Change

The Model 550/500 Python Micro-Pleat Fume Extractor is engineered for heavy-duty, high-volume fume extraction applications. The system is equipped with a 12'L flexible Python hose that provides powerful suction. The magnet capture hood allows the operator to secure the hose inlet to metal surfaces in hard-to-reach places. This unit provides air volume up to 480/375 CFM [cubic feet per minute].

This system comes equipped with cleanable Micro-Pleat Series 1 Particulate Filters and is designed for production applications, including welding (MIG, TIG, Stick, plasma cutting), grinding, powder weighing, some dust collection applications, and fume extraction for classrooms and multiple soldering, welding, and brazing work stations. Extensive research and testing was performed in developing this particulate media filter and is designed for applications that have heavy loading.

The Particulate Filters are engineered to be easily cleaned with pressurized air while they remain installed. The operator simply sprays air into the filters to clean and rejuvenate them. Dust and waste fall into the internal dust pan, making debris removal simple. The included Magnehelic Gage is an excellent tool for determining filter saturation. When the gage shows increasing pressure levels, the operator can clean the filters. The resulting pressure reduction, noted via the gage, indicates the filters are performing as designed.

The Model 550/500 is highly portable and requires no exterior-ducting or makeup air. Heavy-duty, locking casters make this fume extractor the perfect solution for applications that require a powerful respiratory engineering control with maneuverability. A Variable Speed Controller and Magnehelic Gage are standard with this unit



1.800.799.4609  
www.sentryair.com  
sales@sentryair.com

